

High Efficient Soft Mounted Washer Extractor **XP**



FEATURES

- Freestanding, high spin
- Patented Cascade Drum™
- Stainless steel drum and tub
- **xControl Plus** - Fully programmable
- **3rd water inlet, high inlets capacity**
- 2x large drain valves (Ø 76 mm)
- Large door opening for easy loading unloading
- **USB and RS485 plug** (back panel)
- User Friendly control position regardless
- **Bumper** (front side panel)
- Soap hopper
- **Easy Soap** - liquid soaps connection
- Wet Cleaning

OPTIONS

- Stainless steel front
- Liquid soap pumps
- Inclinación hacia adelante (XP45 - XP60)
- Recycle valve
- OPTILOAD™ - weighing system
- Water sample tap
- Steam heating version
- Air operated water inlets
- Grifo para tomar muestras de agua
- Extra signalization (orange light & horn)
- Isolation for energy and noise reduction
- **Trace-Tech®** sistema de trazabilidad y seguimiento en red de la lavandería



Type		XP 35	XP 45	XP 60
INNERDRUM				
Maximum capacity 1:9	kg	39	27	32
Capacity 1:10	kg	35	24	28
Volume	l	350	240	280
Diameter	mm	Ø914	Ø750	Ø750
DRUM SPEED				
Wash	rpm	45	42	42
Extraction	rpm	839	980	915
G - FACTOR				
		360	350	350
HEATING				
Electricity (Standard)	kW	24	18	22
Hot water	°C	90	90	90
Steam	bar	3-8	1-8	1-8
Sound pressure level	dB(A)	<75	<75	<75
Water valves connection	BSP	1"	1"	1"
Water pressure	kPa	100-800	100-800	100-800
Rec. water pressure	kPa	300-500	300-500	300-500
Water inlet	l/min	578	578	20 - 50
Drain valve	outer Ø mm	2x76	2x76	2x76
Flow amount with drain valve	l/min	210	210	210
Steam valve connection	BSP	3/4"	3/4"	3/4"
Steam pressure	kPa	100-800	100-800	100-800
DIMENSIONS				
HxWxD	mm	1925x1315x1270	925x1315x1700	1925x1315x1502
TRANSPORT DATA				
Gross	kg	1170	1490	1640
Net	kg	1010	1350	1500
Volume	m3	4,45	5,14	5,14
Packed (HxWxD)	mm	2125x1425x1470	2125x1425x1700	2125x1425x1700